PRODUCT DATA SHEET

Industrial
OPEN GEAR Lubricant
Stock No. B-00020

BTS B-00020 Open Gear Lubricant penetrates into gears and cables while maintaining uniform consistency to provide premium lubrication. It is formulated to perform in high pressure environments and in high and low temperatures. BTS B-00020 is also a weatherproof formula that will not wash off. It does not require special applicators or heat.

V.O.C.: Compliant with all U.S. State and Federal Regulations

BENEFITS:

- Penetrates & Protects
- Displaces Water
- Weather Proof
- Inhibits Rust, Corrosion, & Wear
- Low & High Temp Protection to 550 °F /288 °F

APPLICATIONS

Open/Exposed Gears	Cables
Power Winches	Pulleys
Hinges & Latches	Wire Ropes
Industrial Equipment	Conveyers
Marine Equipment	

SPECIFICATIONS

Can Size: 16 oz. **Carton Pack**: 12
Net Weight: 12 oz. (340 g) **Extension tube**: No
Fluid Contents: 15.8 oz. (468 mL)

PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Range: -44 °F to 900 °F **Specific Gravity**: (H_20=1): 0.81
Vapor Density: Heavier Than Air **Evaporation Rate**: Slower Than Ether
Solubility in Water: Nil
Appearance/Odor: Aerosol Product Containing Thick Black Liquid/Petroleum
Flash Point: -156 °F **Method Used:** Estimated

HMIS RATINGS

Health	1
Flammability	4
Reactivity	0
Personal Protection	

All information is subject to change. Not responsible for errors.
We recommend you call to verify product specifications before ordering.

R.10/11

Formulating For Professionals for Over 50 Years

BTS Industries, *APEX International Group, Inc* • P.O. Box 14607,
North Palm Beach, FL 33408 www.apexig.com
(561) 656-0850 • Fax: (561) 656-0870 • email: apex@apexig.com
Main Distribution Center – Bridgeview (Chicago), IL © 2012 Apex International Group, Inc.

Made with Pride in the U.S.A.