



PRODUCT DATA SHEET

Performance **CLEAR** Chain & Cable **LUBE**



With PTFE Friction Reducer
Stock No. B-00031

BTS Clear Lube with PTFE is formulated to provide a lubricating film to reduce friction and wear on moving parts and in metal-to-metal contact applications. BTS B-00031 also forms a corrosion inhibiting protective barrier. It will not fly off or break down, and it contains polytetrafluoroethylene (PTFE) for superior lubrication.

V.O.C.: Compliant in all U.S. states except California.

Not for sale or use in California except for OEM Manufacturing.

BENEFITS:

- Reduces Friction & Wear
- Will Not Fly Off or Break Down
- Clear Formula Penetrates to Protect
- Operating Temperatures to +285 °F (141 °C)

APPLICATIONS

Gears	Nuts	Chain Saws	Performance Bicycles
Cables	Bolts	Power Drives	Go Carts
Chains	Hoists	Throttle Cables	Lawn Equipment
Hinges	Winches	Steering Cables	Boat Cables
Bearings	Sprockets	Dies and Molds	Screw Drive Lifts
Fasteners	Wire Ropes	Link and Roller Assemblies	

SPECIFICATIONS

Can Size: 16 oz.	Carton Pack: 12
Net Weight: 11 oz. (312 g)	Extension tube: Yes
Fluid Contents: 15.0 fl. oz. (443 mL)	

PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Range: -44 °F to 500 °F	Specific Gravity: (H ₂ O=1): 0.70
Vapor Density: Heavier Than Air	Evaporation Rate: Slower Than Ether
Solubility in Water: Nil	
Appearance/Odor: Aerosol Product Containing Amber Liquid/Typical Solvent	
Flash Point: -156 °F	Method Used: Estimated

HMIS RATINGS

Health	1
Flammability	4
Reactivity	0
Personal Protection	

*All information is subject to change. Not responsible for errors.
We recommend you call to verify product specifications before ordering.*

R.1/14

Formulating For Professionals for Over 50 Years

BTS Industries, APEX International Group, Inc • P.O. Box 14607,

North Palm Beach, FL 33408 • www.apexig.com

(561) 656-0850 • Fax: (561) 656-0870 • email: apex@apexig.com

Main Distribution Center – Bridgeview (Chicago), IL © 2014 Apex International Group, Inc.



Made with Pride
in the U.S.A.