



PRODUCT DATA SHEET

Industrial Grade O.E. Shiny Galvanize

Bright Zinc Rich Coating

Stock No. B-00062



BTS Industrial Grade O.E. Shiny Galvanize is a Bright zinc-rich coating which bonds a protective layer to metal surfaces. It provides superior, long-term protection against rust and corrosion. BTS B-00062 bonds easily to metal and works by acting as a sacrificial layer – the zinc content oxidizes instead of the metal. It can be used as a touch-up or primer for marred or scratched hot-dip galvanized surfaces or used as a final protective coating.

V.O.C.: Compliant with all U.S. State and Federal Regulations

ASTM SPECS:

Meets ASTM A780-93A Specs

BENEFITS:

- Fast Drying • Dry time*: To Touch: 5 min., To Recoat: 20 min.
 - Prevents Rust & Corrosion • Superior Long Term Protection
 - Chemical & Abrasion Resistant • High Heat Resistance – to 250°
 - Zinc Rich Formula • Durable Acrylic Resin Finish
- * At 72°F, 50% humidity, 1.5 Mil Thickness

APPLICATIONS

Repairs to Hot-Dip Galvanizing	Weldments	Water Tanks
Construction Equipment	Boats	Guardrails
Roofs/Gutters	Ships	Storage Tanks
Off-Shore Drilling Rigs	Fencing	Farm Equipment
Automotive/Truck Bodies	Pipelines	Cell Phone Towers
Spring and Coils	Trailers	Railroad Equipment

SPECIFICATIONS

Can Size: 16 oz.
Net Weight: 13 oz. (369g)
Fluid Contents: 15.6 fl. oz. (461mL)
Shipping Classification: Consumer Commodity ORM-D, UN1950

Carton Pack: 12
Extension Tube: No
Flammability: "Extremely Flammable"

PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: -110°C / -166°F
Vapor Density: Heavier Than Air
Solubility in Water: Slight
Appearance/Odor: Aerosol Product Containing Gray Lacquer
Flash Point: -4°F / -19°C
Zinc Purity: 95+%**Zinc % in Dried Paint Film:** 65.5%

Specific Gravity: (H₂O=1): .87
Evaporation Rate: Slower Than Ether
Method Used: Estimated
Resin System: Acrylic

HMIS RATINGS

Health: 1 Reactivity: 0
Fire: 4 Physical Hazard: 3

*All information is subject to change. Not responsible for errors.
We recommend you call to verify product specifications before ordering.*

06/13

Formulating For Professionals for Over 50 Years

BTS Industries, APEX International Group, Inc • P.O. Box 14607,
North Palm Beach, FL 33408

(561) 656-0850 • Fax: (561) 656-0870 • email: apex@apexig.com

Main Distribution Center– Bridgeview (Chicago), IL © 2013 Apex International Group, Inc.



Made with Pride
in the U.S.A.