PRODUCT DATA SHEET

Street Legal MMT+ Octane Power Boost

Stock No. B-00545

Many of today's engines are monitored by on-board computers to detect and prevent damaging knocks and pings. When these conditions are detected the computer retards ignition timing which reduces performance. It can also sense when the octane is sufficient to advance the timing for more horsepower and performance. BTS Octane Power Boost is formulated to increase Octane up to 15 Points with a true MMT-based Octane Booster. The Dual-Action Formula also cleans injectors, intake valves, and combustion chambers to help reduce the octane requirement of the engine. This combination provides an increased Octane Effect of up to 25 points. In fuel evaluation terms: 10 points equals 1 Octane Number of Fuel Rating. Reduced knock and ping increases engine life and performance. BTS Octane Power Boost also protects against valve seat recession, and contains a smoke suppressant for 2 cycle engines.

- This product is U.S. EPA Registered, safe for catalysts and oxygen sensors, and safe for use in all gasoline engines.
- Use when Top Performance is desired. To help Maintain Performance use every 3000 miles (4800 km.). Use along with other BTS Fuel Additives including BTS Super Concentrated Fuel Injector Cleaner.

TREATMENT:

For EPA Street Legal Treatment Use One Bottle per 21 Gallons
- For Smaller Vehicles or Equipment: One Ounce Treats 1.5 gallons

BENEFITS:

- Stops Knocks & Pings
- Raises Octane up to 1.5 Octane Numbers, or 15 points, with MMT
- Increases Octane Effect up to 25 Points (10 points = 1 Octane Number)
- Dual Action – Cleans & Improves Performance
- Protects against Valve Recession
- Helps Reduce CO & HC Emissions

Note: For Off-Road applications treatment level can be increased to (2) bottles per 21 gal. (2 oz. per 1.5 gal)

APPLICATIONS

Automobiles	Construction Equipment
Marine Engines	Stationary Engines
Trucks & Recreational Vehicles	Lawn & Garden Equipment

SPECIFICATIONS

Bottle Size: 12 oz. **Carton Pack**: 12
Net Contents: 12 fl oz. (350 mL) **Case Weight**: 10 lbs
Shipping Classification: Consumer Commodity, ORM-D, UN1993

PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Pt.: 360°F (182.2°C)-550°F (287.8° C) **Specific Gravity**: ~.86
Vapor Density: <1 **Evaporation Rate**: >1 (BuAC=1)
Solubility in Water: Not Soluble
Flash Point: >140°F (60°C) **Method Used:** Pensky-Marten Closed Cup
Appearance/Odor: Clear Red Liquid / Mild Solvent

HMIS RATINGS

Health: 1	Physical Hazard: 2
Flammability: 2	PPE: G

All information is subject to change. Not responsible for errors.
We recommend you call to verify product specifications before ordering.

Rev. 08/12

Formulating For Professionals for Over 50 Years

BTS Industries, *APEX International Group, Inc* • P.O. Box 14607,
North Palm Beach, FL 33408 www.apexig.com
(561) 656-0850 • Fax: (561) 656-0870 • email: apex@apexig.com
Main Distribution Center – Bridgeview (Chicago), IL © 2013 Apex International Group, Inc.

Made with Pride in the U.S.A.