



PRODUCT DATA SHEET

Medium Strength Removable BLUE Threadlocker Stock No. B-20010



BTS Blue Threadlocker, Medium Strength locks and seals threaded and press fit assemblies to prevent leakage and loosening due to vibration. It resists oils, glycol & water, transmission fluid and mild acids. It is not recommended for plastic.

Conforms to MIL-SPEC MIL-S-46163A
Meets or Exceeds OEM Specs

V.O.C.: Compliant with all U.S. State and Federal Regulations

BENEFITS:

- Locks and Seals Threads
- Prevents Loosening From Vibration
- Removable with Standard Tools
- Fills Gaps up to .007 Inches
- Fastens $\frac{1}{4}$ " to $\frac{3}{4}$ "

APPLICATIONS

All types of threaded connectors to ensure permanent fixing and sealing, especially high vibration and pressurized application. Excellent for all types of engines & pumps and machinery including crankshaft bearing caps, end plates, head and exhaust studs, engine mounts, fasteners and wheel studs.

SPECIFICATIONS

Bottle Size: 10mL

Net Weight: .34fl. oz.

Fluid Contents: .34 fl. oz.

Carton Pack: 12

Extension tube: No

PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Range: >300°F

Vapor Density: Heavier Than Air

Solubility in Water: Nil

Appearance/Odor: Blue Liquid; Mild Organic Odor

Flash Point: >212°F

Fixture & Cure Time: Initial fixture time: Aprox.20 min.

Specific Gravity: (H₂O=1): 1.10

Evaporation Rate: Not Applicable

Method Used: TOC

Full cure: 24 hours

HMIS RATINGS

Health	1
Flammability	1
Reactivity	1
Personal Protection	

*All information is subject to change. Not responsible for errors.
We recommend you call to verify product specifications before ordering.*

Formulating For Professionals for Over 50 Years

BTS Industries, APEX International Group, Inc • P.O. Box 14607,

North Palm Beach, FL 33408 www.apexig.com

(561) 656-0850 • Fax: (561) 656-0870 • email: apex@apexig.com

Main Distribution Center – Bridgeview (Chicago), IL © 2013 Apex International Group, Inc.



Made with Pride
in the U.S.A.

R. 12/11