

PRODUCT DATA SHEET

BTS Blue Threadlocker, Medium Strength locks and seals threaded and press fit assemblies to prevent leakage and loosening due to vibration. It resists oils, glycol & water, transmission fluid and mild acids. It is not recommended for plastic.

Conforms to MIL-SPEC MIL-S-46163A
Meets or Exceeds OEM Specs. Compare to LOCTITE 242.

V.O.C.: Compliant with all U.S. State and Federal Regulations

- ### BENEFITS:

- Locks and Seals Threads
- Prevents Loosening From Vibration
- Removable with Standard Tools
- Fills Gaps up to .007 inches
- Fastens 1/4 " to 3/4 "

APPLICATIONS

All types of threaded connectors to ensure permanent fixing and sealing, especially high vibration and pressurized application. Excellent for all types of engines & pumps and machinery including crankshaft bearing caps, end plates, head and exhaust studs, engine mounts, fasteners and wheel studs.

SPECIFICATIONS

Bottle Size: 50mL
Net Weight: 1.69fl. oz.
Fluid Contents: 1.69 fl. oz.

Carton Pack: 10
Extension tube: No

PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Range: >300°F	Specific Gravity: (H2O=1): 1.10
Vapor Density: Heavier Than Air	Evaporation Rate: Not Applicable
Solubility in Water: Nil	
Appearance/Odor: Blue Liquid; Mild Organic Odor	
Flash Point: >212° F	Method Used: TOC

HMIS RATINGS

Health	1
Flammability	1
Reactivity	1
Personal Protection	

*All information is subject to change. Not responsible for errors.
We recommend you call to verify product specifications before ordering.*

Formulating For Professionals for Over 50 Years

BTS Industries, APEX International Group, Inc www.apexig.com

(561) 656-0850 • Fax: (561) 656-0870 • email: apex@apexig.com

© 2017 Apex International Group, Inc.

BTS® is sold throughout the world under the APEX registered trademark BTS.



Made with Pride
in the U.S.A.

R. 12/11