



PRODUCT DATA SHEET

High Strength RED Threadlocker Stock No. B-20150



BTS Red Threadlocker, High Strength locks and seals threaded and press fit assemblies to prevent leakage and loosening due to vibration. It resists oils, glycol & water, transmission fluid and mild acids. It is not recommended for plastic.

Conforms to MIL-SPEC MIL- S-46163A
Meets or Exceeds OEM Specs

V.O.C.: Compliant with all U.S. State and Federal Regulations

BENEFITS:

- Locks and Seals Threaded Connections
- Prevents Loosening From Vibration
- Requires Extra Effort for Removal
- Fills Gaps up to .007 Inches
- Fastens 3/8" to 1 "

APPLICATIONS

All types of threaded connectors to ensure permanent fixing and sealing, especially high vibration and pressurized application. Excellent for all types of engines & pumps and machinery including crankshaft bearing caps, end plates, head and exhaust studs, engine mounts, fasteners and wheel studs.

SPECIFICATIONS

Bottle Size: 50mL
Net Weight: 1.69 fl. oz.
Fluid Contents: 1.69 fl. oz.

Carton Pack: 10
Extension tube: No

PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Range: >300°F
Vapor Density: Heavier Than Air
Solubility in Water: Nil

Appearance/Odor: Red Liquid; Mild Organic Odor

Flash Point: >212° F

Specific Gravity: (H₂O=1): 1.10
Evaporation Rate: Not Applicable

Method Used: TOC

Fixture & Cure Time: Initial fixture time: Aprox.10 min. Full cure: 24 hours

HMIS RATINGS

Health	1
Flammability	1
Reactivity	1
Personal Protection	

*All information is subject to change. Not responsible for errors.
We recommend you call to verify product specifications before ordering.*

Formulating For Professionals for Over 50 Years

BTS Industries, APEX International Group, Inc • P.O. Box 14607,
North Palm Beach, FL 33408 www.apexig.com

(561) 656-0850 • Fax: (561) 656-0870 • email: apex@apexig.com

Main Distribution Center – Bridgeview (Chicago), IL © 2013 Apex International Group, Inc.



Made with Pride
in the U.S.A.

R. 12/11